



# FUNGICIDAL COATING

Designed to Kill Residual Mold and Mildew\*

<b>ACTIVE INGREDIENT:</b>	
Chlorothalonil .....	0.48%
<b>OTHER INGREDIENTS:.....</b>	<b>99.52%</b>
<b>TOTAL:.....</b>	<b>100.00%</b>

NET CONTENTS: 1 Gallon (3.78 L)

**Keep Out of Reach of Children**

**CAUTION:** See back panel for additional precautionary statements

EPA Reg. No. 73884-1 EPA Est. No. 73884-MA-1

AfterShock is an extremely durable acrylic finish, developed to withstand moist humid conditions that provide the ideal environment for fungal growth. This easy to apply coating offers the ultimate in durability in combination with excellent fungicidal characteristics.

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Check with all local, state, and federal regulations before beginning work or using this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult with a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

\*AfterShock is designed to kill residual mold and mildew remaining after precleaning contaminated surfaces, as well as to inhibit the future growth and spread of mold and mildew on the cured film surface in residential & institutional buildings. AfterShock is recommended for use on interior wall surfaces such as plaster, wallboard, Sheetrock®, concrete, masonry block, wood, primed metal and galvanized metal. AfterShock is also recommended for use on interior wood framing, primed metal, concrete, and wallboard inside the wall cavity. Do not use for HVAC system application.

**SURFACE PREPARATION**

AfterShock is supplied ready to use. Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. Remove damaged materials and clean surfaces. Patch surface irregularities with an appropriate patching compound. AfterShock is self-priming over bare gypsum drywall, composition board, ceiling tile and concrete. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation during application.

**APPLICATION TOOLS**

Apply AfterShock with brush, roller or airless spray equipment. If using airless spray equipment, AfterShock can be successfully applied with a .017- .019 tip setting.

**COVERAGE**

- Smooth Surfaces: 300-350 ft<sup>2</sup> per gallon
- Porous Surfaces: 175-300 ft<sup>2</sup> per gallon
- Spray: 50% of above

**MOLD & MILDEW CONTROL**

Remove gross filth or heavy soil. For heavily soiled areas, a pre-cleaning step is required. Apply AfterShock generously and uniformly by brush or airless spray and ensure that the surface is completely coated. Allow to air dry. Clean and inspect regularly for damage to coating film- reapply if cured coating film becomes damaged. AfterShock will kill all existing visible mold and mildew on the wall surface, and then will prevent the growth of mold and mildew on the surface of the cured film.

**DRYING TIME @ 70°F 50% R.H**

To Touch: 1 Hour

**CLEANUP**

Clean tools and drippings with warm soapy water before AfterShock dries.

**8390-1 White**

**Storage and Disposal**

Do not contaminate water, food or feed by storage or disposal.

**Pesticide Storage:** Close container after each use. Keep from freezing.

**Pesticide Disposal:** Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

**Container Disposal:** Nonrefillable containers. Do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

**Proposition 65 Warning:** This product contains a chemical(s) known to the State of California to cause cancer.

FIRST AID	
Have the product label or MSDS with you when calling a poison control center or doctor, or going for treatment.	
<b>IF IN EYES:</b>	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice.
<b>IF INHALED:</b>	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
<b>IF SWALLOWED:</b>	Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.
<b>IF ON SKIN OR CLOTHING:</b>	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
<b>FOR MEDICAL ASSISTANCE, CALL YOUR LOCAL POISON CONTROL CENTER or 800-222-1222</b>	

**PRECAUTIONARY STATEMENTS**  
HAZARDS TO HUMANS  
**CAUTION**

Harmful if swallowed or inhaled. Avoid breathing spray mist. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse. When applying with a sprayer, applicator should wear a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, N, or HE filter.

**PHYSICAL AND CHEMICAL HAZARDS**

Do not apply this product in or on electric equipment due to the possibility of shock hazard.

<b>CAS. No.:</b>	<b>CHEMICAL INGREDIENTS:</b>
7732-18-5	Water
13463-67-7	Titanium dioxide
25265-77-4	2,2,4-Trimethyl-1,3-Pentenediol Monoisobutyrate
57-55-6	Propylene glycol
Not available	Latex resin solids*

\*Contents partially unknown

Max VOC Content: 200 g/l



Manufactured By:  
**Fiberlock Technologies, Inc.**  
Andover, MA 01810  
(800) 342-3755  
www.fiberlock.com

ESL042209 REV040315