

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



IAQ 6040 is a low-viscosity, translucent violet, mold resistant sealant designed for use on new construction materials.* This specially formulated, water based coating contains a fungistatic agent to resist mold growth on the dry coating surface. The low-viscosity 100% acrylic formula is easy to apply, and the translucent finish will not block the appearance of coated building materials. IAQ 6040 can be applied to wood, OSB, wallboard, concrete and other construction materials.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWaveRTU.

APPLICATION TOOLS

Apply IAQ 6040 with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer
- Spray: .015 to .021 tip @ 1500-2000 P.S.I.

PRODUCT APPLICATION

IAQ 6040 is supplied ready to use, but can be thinned sparingly with water (up to 8 oz. water per gallon) for proper application consistency if necessary. Apply one coat of IAQ 6040 generously and uniformly by airless spray or brush or roller to ensure that the finished surface is properly sealed. Two-coats may be

required on some porous surfaces.

COVERAGE

- Smooth Surfaces: 400-450 ft²/gal.
- Porous Surfaces: 200-300 ft²/gal.

DRYING TIME @ 70°F 50% R.H

- To Touch: 1-2 hours
- Recoat: 8-16 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 6040 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. IAQ 6040 is resistant to the deteriorating action of mold and mildew. No claim is made for the preservative action to other than the coating film. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.

Fiberlock
TECHNOLOGIES

Professional Products
Professional Results



6040

Mold Resistant Sealant*
VIOLET

- Highly permeable

- Class A fire rated

*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

CAS. No.:

7732-18-5
12174-11-7
25265-77-4
57-55-6
Not Available†

CHEMICAL INGREDIENTS:

Water
Magnesium aluminum silicate
2,2,4-Trimethyl-1,3-Pentenediol Monoisobutyrate
Propylene glycol
Latex resin solids

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

†Contents partially unknown

Calculated VOC: 89 g/l

WARNING:



Hazard Statements:

Harmful if inhaled.
Causes mild skin irritation.
Causes serious eye irritation.
May cause cancer.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924
(Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of IAQ 6040, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

8363-5
Violet



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com