

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



IAQ 9000 is a white waterproofing coating that is specially formulated to stop water from penetrating through a variety of interior and exterior surfaces including above or below grade masonry walls, cinder and concrete blocks, stucco, brick, retaining walls, basements, and foundations. This latex based formula stops 10 psi of water pressure (greater than a wall of water 22 feet high). IAQ 9000 contains a fungistatic agent to resist mold growth on the surface of the coating. This fast-drying formula may be applied with a brush and/or roller on dry surfaces and cleans up easily with soap and water.

#### SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop and HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD(5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWaveRTU.

Patch irregularities with an appropriate patching compound. Efflorescence, a white, powdery, crystal-like deposit visible on masonry surfaces, must be removed. Muriatic acid, used according to manufacturer's directions, is an effective efflorescence removal agent.

#### PRODUCT APPLICATION

STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN. For best results, use a 5 in. paddle wheel mixer, attached to a 1/2 horsepower, 1/2 inch electric drill. Coat surface only when air and surface temperatures are 50°F or higher. Apply IAQ 9000 directly on bare masonry. For best waterproofing results, wait for a dry (rain-free) period before application. Apply first coat with a good quality nylon bristle brush, working the waterproofer into the pores of the masonry - avoid excessive brushing. Allow to dry 3 hours before second coat. The second coat may be applied using brush, roller or spray. If leaking is still present

after two coats, it indicates that pores or pinholes are still open. These areas should be coated again. Vent outside.

#### SPRAY APPLICATION

IAQ 9000 may be applied by spray to exterior and interior surfaces, providing certain precautions are followed. Specialized spray equipment is required, please refer to IAQ 9000 Spray Instructions sheet for specific details (Contact Fiberlock for more information). Do not attempt to apply with conventional airless spray equipment due to the abrasive properties of IAQ 9000.

#### TINTING

May be tinted to light or pastel shades with alkali-proof universal tinting colors. Use only 25% of color normally recommended. Do not use more than 2 fl. oz. of colorant per gallon. IAQ 9000 is ideal as a finish coat.

#### COVERAGE

- Smooth Surfaces:
  - 1st coat: 100-125 ft<sup>2</sup>/gal.
  - 2nd coat: 125 ft<sup>2</sup>/gal.
- Porous Surfaces:
  - 1st coat: 75 ft<sup>2</sup>/gal.
  - 2nd coat: 125 ft<sup>2</sup>/gal.

#### DRYING TIME @ 70°F 50% R.H

- To Touch: 1 hour
- Recoat: 3 hours

#### CLEANUP

Clean application tools immediately after use in warm, soapy water. Dispose of waste according to all existing local, state and federal regulations.

#### PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. IAQ 9000 is resistant to the deteriorating action of mold and mildew. No claim is made for the preservative action other than to the coating film. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.

# Fiberlock

TECHNOLOGIES

Professional Products  
Professional Results



# 9000

## Mold Resistant Masonry Waterproofer\*

- Holds back 10 PSI of water pressure
- Tintable
- Latex based formulation
- For interior or exterior use

\*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

**DANGER!**  
**KEEP OUT OF REACH OF CHILDREN.**  
Do not take internally. Close container after each use.  
Keep from freezing.  
Store between 40°F (4.5°C) and 90°F (32°C)  
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

CAS. No.:  
7732-18-5  
111-77-3  
85-68-7  
25036-16-2  
13463-67-7

**CHEMICAL INGREDIENTS:**  
Water  
Diethylene Glycol Monomethyl Ether  
Butyl Benzyl Phthalate  
Styrene Acrylic Resin  
Titanium Dioxide

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Calculated VOC: <100 g/l

#### DANGER:



#### Hazard Statements:

Harmful if swallowed.  
Harmful if inhaled.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
May cause cancer.

#### Precautionary Statements:

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray.

**Response:** If exposed or concerned: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an approved waste disposal plant.

**Emergency Tel. No.:** CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of IAQ 9000, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

# 8395-5 White



150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)