



Professional Products,
Professional Results

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



Leadsafe Wipes are excellent for use anywhere lead dust from deteriorated paint may be present, such as:

Walls	Stairs	Floors	Windows	Doors
Blinds	Railings	Fences	Gates	Moldings
Trim	Baseboards	Ceilings	Sills	Porches

Designed for use by:

Abatement Contractors	Home Owners	Painting Contractors
Building Owners	Public health Inspectors	Apartment Renters
Environmental Specialists		

Permanent Lead Abatement Paint

LBC & ChildGuard - Permanent lead abatement coatings which offer unparalleled coverage, economics and paint-like aesthetics while preserving historic and architectural detail. Both LBC & ChildGuard contain Bitrex®, a bitter-tasting anti-ingestant to discourage oral contact with the coating.

Lead Dust Cleaner

LeadSafe Cleaner - A concentrated product designed specifically to assist in the cleanup of lead dust after lead abatement projects, construction, renovation or any other activity which disturbs lead and creates dust. Lead dust residues are heavier than everyday dust and are therefore harder to "pick up" with traditional cleaning agents. Typical household cleaners either drive lead residues deeper into a surface or simply spread them around as you wipe.

To truly clean lead dust you need to first pull the lead away from a substrate and then hold it in suspension so that it can be wiped away. LeadSafe Lead Dust Cleaner utilizes a proprietary formulation of citric acid and chelating agents that do just that. First, the citric acid breaks the surface tension and lifts the lead away from the substrate, then the chelating agents bind with the lead so they remain in suspension and can be easily wiped away.



LEAD DUST WIPES

Formulated To Control and Remove Lead Dust



- More effective at removing lead dust than traditional cleaning wipes

- Faster cleanup and compliance
- Lifts lead dust out of the substrate

NET CONTENTS: 90 Wipes (8"x12")

For Professional Use Only

Lead Abatement Products

5498-90C



6 11131 95469 0



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com

LeadSafe Lead Dust Wipes are conveniently packaged towelettes presoaked in a trisodium phosphate (TSP) solution to aid in surface preparation and cleaning for the quick removal of harmful lead dust. LeadSafe Wipes are ideal for use before and after any lead abatement project and are a critical part of a conscientious program for the Interim Control of lead-based paint dust hazards. LeadSafe Wipes meet all Federal, State, HUD and EPA guidelines for cleaning and removing lead dust.

DIRECTIONS

Remove container cover, remove and discard seal. From center of roll, pull up corner of towel, twist to a point and thread through hole in underside of cover. Replace cover tightly. Pull up towel and tear at perforation. Wipe lead dust clean away from surface.

NOTE: Trisodium Phosphate can degloss substrates including painted surfaces, plastics, and soft metals. Always test target material in an inconspicuous area prior to use.

CAUTION: Irritating to skin. Avoid prolonged or repeated breathing of vapor. When removing lead dust, wear long pants, long sleeved shirt, shoes and chemical resistant disposable gloves. Wash hands thoroughly with soap and water after use. Dispose of gloves and LeadSafe Lead Dust Wipes after use in accordance with applicable local, state and federal regulations. Launder contaminated clothes separately from other laundry.

FIRST AID

If on skin, wash thoroughly with soap and water. If swallowed, induce vomiting and get medical attention. If in eyes, rinse thoroughly.

Warning: Children and pregnant women should never participate in any activity which could result in them contacting or ingesting lead, lead-based paint or lead dust. All individuals should wear rubber gloves during lead abatement or clean up. If ingested, lead dust can result in lead poisoning. Wash hands, face and any exposed skin before starting any other activity including eating or drinking. Contact federal, state and local environmental agency to determine the appropriate method to dispose of all contaminated materials including mops, rags, sponges, buckets, clothing, rinse water, cleaning solution and clothing. Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C).

DANGER:



Hazard Statements:
Causes skin irritation.
Causes serious eye damage.

Precautionary Statements:

Prevention: Wash hands thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. In case of fire: Use dry chemical, foam, CO2 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container to licensed waste handling facility.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of this product, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

LeadSafe™, the LeadSafe™ Logo and other marks in this label are trademarks of ICP Construction, Inc.