

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



Piranha 2 is a heavy duty, fast acting paint remover for the professional. Utilizing the power of methylene chloride, Piranha 2 will attack multiple layers of paint in a single application. Piranha 2 will remove most oil and latex paints, varnishes, shellacs, lacquers and enamels. Piranha 2 is non-flammable and will not raise the grain of wood or corrode metals. This product does not require anti-evaporation paper like many caustics or other weaker solvent formulas.

#### SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

For indoor application, open all windows and doors or use other means to assure a constant supply of fresh moving air during use. Do not use Piranha 2 in poorly ventilated areas. Ideal working temperature is between 65°- 85°F. Avoid direct sunlight. Protect floor coverings and other areas not being stripped. Do not use on synthetic fabrics, plastic, linoleum, asphalt, foam products or rubber tile.

#### APPLICATION TOOLS

Apply Piranha 2 with brush or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Spray: .017 to .021 tips

#### PRODUCT APPLICATION

Stir well before using. Open pail carefully to avoid splashing. For best results, test a small area to determine the appropriate thickness, and duration of time required to most effectively remove the lead-based paint. Brush on a thick layer in one direction for best results. Brushing back and forth opens up the anti-evaporation barrier, which forms on the initial pass.

Allow Piranha 2 to work 5-15 minutes before performing a test scrape to determine how much paint has been lifted. Once Piranha 2 finishes removing the paint from the surface, scrape it away with putty knife, cloth or steel wool. Clean substrate with a mild detergent solution to remove any residues. Collect waste in a metal container and dispose of all waste in accordance with existing regulations. Piranha 2 does not require a neutralizer.

#### COVERAGE

- Smooth Surfaces: 100 ft<sup>2</sup>/gal.
- Porous Surfaces: 50-100 ft<sup>2</sup>/gal.

#### CLEANUP

Clean tools with a mild detergent solution to remove any residues. Dispose of all waste according to all existing local, state and federal regulations.

#### PRECAUTIONS

**PRECAUTIONS: POISON. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPORS ARE HARMFUL. SKIN AND EYE IRRITANT. CONTAINS METHYLENE CHLORIDE, 2-BUTOXYETHANOL, METHANOL, TOLUENE. CANNOT BE MADE NONPOISONOUS. USE ONLY WITH ADEQUATE VENTILATION (MOVING FRESH AIR).** Methylene chloride has been shown to cause cancer in laboratory animals. Risk to your health depends on level and duration of exposure. Spray application will increase concentration of methylene chloride vapors. Avoid breathing vapors and spray mists. Wear proper respiratory protection. Wear full body, protective clothing for spray application. For indoor application, open all windows and doors or use other means to assure a constant supply of moving fresh air during use. Do not use in basement or other unventilated areas. If eyes water or nose becomes irritated, ventilation is inadequate. Avoid contact with skin or eyes. Exposure to open flame or hot surfaces may produce toxic gases. Open container carefully and close after each use. Store Piranha 2 in original, labeled container only. Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Do not use on plastics. After unusually long exposure to the atmosphere, the material may dry out and become combustible.

**NOTICE:** Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

#### FIRST AID

**EYE:** Immediately flush eyes with clean water for at least 15 minutes. If irritation persists, call a physician immediately.

**SKIN:** In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

**INGESTION:** If ingested, DO NOT induce vomiting; call a physician immediately. Poisonous if swallowed. Can affect the optic nerve resulting in blindness. Can cause mental sluggishness, nausea and vomiting leading to severe illness, possibly death.

**INHALATION:** Remove victim to fresh air. Give oxygen if there is difficulty breathing. Seek medical advice immediately. Refer to the Safety Data Sheet (SDS) available from your distributor or at [www.fiberlock.com](http://www.fiberlock.com) for further safety and handling instructions.

# Fiberlock

TECHNOLOGIES

Professional Products  
Professional Results

# PIRANHA

# 2

## HEAVY DUTY PAINT STRIPPER

### Fast Acting Solvent Based Paint Remover

- Attacks up to 30 layers of paint
- Does not raise the grain of wood

NET CONTENTS: 5 Gallons

For Professional Use Only

Paint Removal Products

CAS. No.:  
108-88-3  
75-09-2  
67-56-1  
111-76-2

**CHEMICAL INGREDIENTS:**  
Toluene  
Methylene chloride  
Methanol  
2-Butoxyethanol

UN1593, Dichloromethane solution, 6.1 PG III - Poison

#### DANGER: POISON!



#### Hazard Statements:

May be fatal or cause blindness if swallowed. Vapor Harmful. Skin and eye irritant.

Use outdoors if possible. If you must use indoors, open all windows and outside doors. Use only with moving fresh air cross ventilation over the work area and across floor.

Keep away from heat and flames.

Vapors flow along floors, under doors and on contact with flame or hot surface. May produce toxic poisonous gas and destroy metals.

#### Precautionary Statements:

**Prevention:** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Response:** If exposed or concerned: Get medical advice/attention.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Emergency Tel. No.:** CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of Piranha 2, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

Piranha, the Piranha Logo and other marks on this label are trademarks of ICP Construction, Inc.

# 5720-5



5720-5



150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.