

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



Fiberlock
TECHNOLOGIES

Professional Products
Professional Results

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

CAS. No.:
7732-18-5
13463-67-7
107-21-1
1314-13-2
1317-65-3
Not avail.

CHEMICAL INGREDIENTS:
Water
Titanium dioxide
Ethylene glycol
Zinc oxide
Calcium carbonate
* Latex resin solids

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

*Contents partially unknown

Calculated VOC: 98 g/l

WARNING:



Hazard Statements:
Harmful if inhaled.
Causes mild skin irritation.
Causes serious eye irritation.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of *PowerBlock™*, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

PowerBlock™, the PowerBlock™ Logo and other marks on this label are trademarks of ICP Construction, Inc.

5450-5
White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com



POWER BLOCK

Interior & Exterior
Stain Blocking Primer

• Superior stain blocking

• Excellent adhesion to glossy surfaces

NET CONTENTS: 5 Gallons

For Professional Use Only

Industrial Coatings & Primers