

# Instant MOLD STAIN REMOVER

Instant Mold Stain Remover is an aggressive stain remover designed to clean stains from mold and mildew within minutes of application. The proprietary formulation instantly targets deeply embedded mold stains, which saves the applicator time and labor.

Works on wood and concrete substrates. Ideally suited to mold stained attic sheathing and basement areas.

- Targets & removes deeply embedded stains from mold and mildew\*
- Works within minutes of application
- No scrubbing required
- Ideal for attic roof sheathing and basement areas
- For indoor and outdoor use



*\*No claim is made by this product to prevent, destroy, repel or mitigate any living organism.*

800.342.3755 - [www.fiberlock.com](http://www.fiberlock.com)

## Instant Mold Stain Remover

Aggressively Removes Stains from Mold and Mildew

8317

Instant Mold Stain Remover is an aggressive stain remover designed to clean stains from mold and mildew within minutes of application. The proprietary formulation instantly targets deeply embedded mold stains, which saves the applicator time and labor. Works on wood and concrete substrates. Ideally suited to mold stained attic sheathing and basement areas.

### DIRECTIONS

ALWAYS USE WITH PROPER VENTILATION AND PPE. CONSULT SAFETY DATA SHEET (SDS) FOR DETAILED PRECAUTIONARY INFORMATION. NEVER MIX FIBERLOCK INSTANT MOLD STAIN REMOVER WITH ANY OTHER PRODUCT. AVOID OVERSPRAY AND DRIPPINGS ON NON-TARGET MATERIAL TO AVOID BLEACHING OR CORROSION ON METALS.

NO CLAIM IS MADE BY THIS PRODUCT TO PREVENT, DESTROY, REPEL OR MITIGATE ANY LIVING ORGANISM.

### PRODUCT APPLICATION

1. Substrate should be cleaned of all gross filth and grime prior to application of Instant Mold Stain Remover.
2. Apply undiluted for maximum stain removal. Apply with a pump sprayer that is resistant to the corrosive effects of sodium hypochlorite.
3. Coverage is 200-500 sq. ft. per gallon depending on substrate porosity.
4. Contain and remove all excess overspray and drippings to avoid bleaching of non-target material (e.g. fabric and carpets).
5. Multiple applications may be required on heavily stained material.
6. Rinse well and air dry.

### PRECAUTIONS

**DANGER! KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY.** Always take care to avoid skin and eye contact by using protective measures such as nitrile rubber gloves (or equivalent) and safety glasses. Do not take internally. Close container after each use. Keep from freezing. Do not return unused product to the original container. Do not store at temperatures above 100°F. Properly dispose of all waste and unused product in accordance with Local, State and Federal regulations. For additional information and/or precautions check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

24 hour Emergency "CHEM-TEL" Phone:  
1-800-255-3924

**Fiberlock Products and CPVC Compatibility**  
Manufacturers of chlorinated polyvinyl chloride ("CPVC") pipe believe that it can be sensitive to or incompatible with chemicals found in many commonly used household and industrial cleaning products, coatings, adhesives and other compounds, and that those chemicals can cause stress cracks or pipe failure. Fiberlock recommends that users always check pipe for markings that indicate the type of material it is made of and that users contact the pipe manufacturer directly before applying any Fiberlock products to CPVC pipe.

### Properties

#### Product Specifications

Active Ingredient(s):	Sodium Hypochlorite
Color:	Straw
Odor:	Chlorine
Flash Point:	None
pH:	12-14
Shelf Life:	6 Months Min. (Original Sealed Container)

#### Coverage

Smooth Surfaces:	200-500 ft <sup>2</sup> /gal
------------------	------------------------------

#### Available Package Sizes

1 gallon containers / 4 per case
----------------------------------