



Provided By:



Application of Piranha NexStrip By Titan Tools, November 2013

| Product Tested | Piranha NexStrip |
|--|---|
| Sprayer Used | Titan Impact 1140/840 |
| Tip Size | 523-527 |
| Gun | LX 80 |
| Hose Length | 50 ^{FT} 3/8 hose with 1/4 whip |
| Paint Sprayer Pressure | 3200 PSI |
| Air Compressor Pressure | N/A |
| Temperature of Environment | 90+ |
| Indoor or Outdoor | Indoor/Outdoor warehouse |
| Did product need to be reduced? | No |
| Did equipment need adjusting? | Remove Filters |
| Thickness of Coating? | 523 Tip, 24 Wet mils, 1 pass |
| Description of Technique used to spray | 8-12 inches from surface |
| Settings Used for Best Results | Above |

Fiberlock recommends Titan Sprayers
For the best application of all Fiberlock Products

Notes and Comments:

- 523 - 527 tip works best
- Upon clean up noticed buildup around inlet screen removing inlet screen may help keep the product moving
- Product can hang inside the pickup tube thorough cleaning is recommended. I even removed the lower half and noticed build up around cage and seat however cleans up really well with slight agitation
- Also tested with Titan 840 with 1/4 hose and 523 and exceeded my expectations, this product could be sprayed with an Titan Impact 840

