

Wet-Wrap 'N' Seal is a permanent, water-activated insulation encasement and repair system. It applies quickly and easily to pipes, breeching, valves, duct work and other fittings. When dried it permanently retains its strength and form. Wet-Wrap 'N' Seal is the most cost-effective encasement available, saving time and labor, requiring no maintenance, special tools or skills and leaving no waste.

SURFACE PREPARATION

Prior to application it is important to determine if the existing asbestos matrix is well adhered to the substrate. Correct any surface defects and clean all surfaces thoroughly. Be careful not to agitate asbestos fibers during preparation; this could increase asbestos exposure.

If damaged, first apply a light collating of SerpiFlex followed by a second application. The second application should saturated the damaged area.

Apply additional fiberglass, mineral wool or insulation cement to treated area if needed.

PRODUCT APPLICATION

Water in pail must be clean at all times. This product is a plaster of paris and synthetic resin combination. Use of skin protection or gloves is recommended.

1. Hold loosely and submerge one Wet-Wrap 'N' Seal roll at a time in clean, tepid water (68°F/20°C) for 5 seconds. Keep thumb under edge of Wet-Wrap 'N' Seal to avoid difficulty in finding starting end after squeezing.
2. Remove and squeeze with twisting motion to wring out excess water, keeping thumbs under starting end.
3. When applying overlap each layer by 50%. Smooth each overlap turn of Wet-Wrap 'N' Seal into the layers below, molding carefully to the contour, forming a solid, well-fused covering.

Note: For leather-tough protection and added strength, you can apply SerpiMastic over the Wet-Wrap 'N' Seal after it is dry

SETTING TIME

Wet-Wrap 'N' Seal will set in 2-4 minutes. Setting time is measured from the point when the product is immersed to the point when it can no longer be molded. Increasing or decreasing the temperate of the immersion water by 9°F (5°C) will reduce or extend the setting time by approximately 15 seconds.

CLEANUP

Tools and drippings should be cleaned with warm soapy water before adhesive dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.



Wet-Wrap 'N' Seal

WATER ACTIVATED ENCASEMENT REPAIR CLOTH

6" Wide

- Applies quickly and easily
- Free of fumes and odors
- Permanently shaped
- High strength
- Pre-cut to 9 ft (2.7m) lengths
- One-step installation
- Saves time and labor
- No maintenance
- No waste
- No special skills or tools required

For Professional Use Only

2433-U 6"x9' (40 Rolls)



**CAUTION!
KEEP OUT OF REACH OF CHILDREN.**

Do not take internally.
Close container after each use.
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

**FIBERLOCK WET-WRAP 'N' SEAL 2433
WARNING | ATTENTION**



H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.

Use only outdoors or in a well-ventilated area.; Avoid breathing dust/fumes.; Wear protective gloves/ protective clothing/eye protection/face protection.; See SDS for full list of P phrases

Specific treatment (see advice on this label); Take off contaminated clothing and wash before reuse.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; Call a POISON CENTER or doctor/physician if you feel unwell.; If eye irritation persists: Get medical advice/attention.; IF ON SKIN: Wash with plenty of soap and water.; See SDS for full list of P phrases

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of this product, for each specific project and for the health and safety of personnel working in the area.

For additional information check Material Safety Data Sheet (MSDS) or Product Data Sheet (PDS) available online at www.serpisystems.

Wet-Wrap 'N' Seal, the Wet-Wrap 'N' Seal Logo and other marks in this literature are trademarks of Fiberlock Technologies, Inc.



ICP
CONSTRUCTION
150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.17.18