

- Superior Smoke Odor Blocking
- Superior Stain Blocking
- Blocks Pet Odors

- Superior Application Characteristics
- Superior Recoat-Ability
- Easily Topcoated



Professional Products  
Professional Results

**DANGER!**  
**KEEP OUT OF REACH OF CHILDREN.**  
Do not take internally.  
Close container after each use.  
Keep from freezing.  
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

Calculated VOC: 49 g/l

**FIBERLOCK ULTRA RECON SMOKE ODOR SEALER WHITE 3092**  
**WARNING | ATTENTION**



H319 - Causes serious eye irritation.  
H351 - Suspected of causing cancer.  
H412 - Harmful to aquatic life with long lasting effects.

H319 - Provoque une sévère irritation des yeux.  
H351 - Susceptible de provoquer le cancer.  
H412 - Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Obtain special instructions before use.; Use personal protective equipment as required.; Avoid release to the environment.; Wear protective gloves/protective clothing/eye protection/face protection.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation. | Utiliser l'équipement de protection individuel requis. | Éviter le rejet dans l'environnement. | Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage. | Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; If eye irritation persists: Get medical advice/attention.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin. | EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. | Si l'irritation oculaire persiste: consulter un médecin. | Voir SDS pour la liste complète des phrases P

**Canadian Contact Info:**  
**4050-B Sladeview Crescent Suite 200**  
**Mississauga, ON L5L 5Y5 Canada**

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

For Technical Information call 800.342.3755  
These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of this product, for each specific project and for the health and safety of personnel working in the area.  
For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

Fiberlock Technologies, the Logo and other marks on this label are trademarks of ICP Construction, Inc.

**3092-5**  
**White**



**ICP**  
CONSTRUCTION  
150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)  
Rev. 10.17.18



Roller: 3/8" Nap Synthetic Fiber  
Spray Settings:  
Pressure: 2000-3000 P.S.I.  
Tips: .015 to .021 tips

**PRODUCT APPLICATION**

Apply ULTRA RECON Smoke Odor Sealer generously and uniformly by brush, airless spray or roller. Apply one coat of ULTRA RECON Smoke Odor Sealer and ensure that the finished surface is properly sealed. Two-coats may be required on some porous or heavily stained surfaces. Topcoat floor applications when foot traffic or heavy storage is expected. ULTRA RECON Smoke Odor Sealer is tintable up to 2 oz. of universal liquid colorant per gallon. Can be directly applied to wallboard, sheetrock, wood, masonry and concrete. Ferrous metals may require a DTM primer to prevent flash rusting. Topcoat with water or oil-based paints. Not for use in HVAC systems.

**COVERAGE**

Smooth Surfaces: 200-400 ft<sup>2</sup>/gal.  
Porous Surfaces: 100-200 ft<sup>2</sup>/gal.

**DRYING TIME @ 70°F 50% R.H**

To Touch: 30 Min.  
Recoat: 2 Hours  
Topcoat: 2 Hours

**CLEANUP**

Clean tools and drippings with warm soapy water before ULTRA RECON Smoke Odor Sealer dries. The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

**PRECAUTIONS**

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F. (32°C). Keep closures tight and containers upright to prevent leakage. Product is non-combustible. Stir thoroughly. Do not mix with any other coatings, additives, solvents or colors in oil. Do not apply when air or surface temperature is below 45°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content. In areas with high humidity, apply when surface temperature is 45°F or higher. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter.

**SURFACE PREPARATION**

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Prior to applying Fiberlock's ULTRA RECON Smoke Odor Sealer (Ultra SOS™) it is critical that the substrate be thoroughly cleaned. Smoke odor encapsulation is a final step that needs to be part of a comprehensive smoke/odor management protocol. This protocol should include the following steps: Odor Cleaning, Odor Neutralization and Odor Encapsulation.

Fiberlock recommends cleaning with RECON Heavy Duty Cleaner or Extreme Duty Cleaner, followed by the application of RECON Extreme Duty Odor Counteractant. After the substrate is clean, dry and sound, apply ULTRA RECON Smoke Odor Sealer to encapsulate any residual odors that remain.

**APPLICATION TOOLS**

Apply ULTRA RECON Smoke Odor Sealer with a brush, roller or airless spray equipment.  
Brush: Synthetic, nylon or polyester bristle



Universal Restoration Primer/Sealer

Permanently Encapsulates Smoke Odors On Structural, Finished and Decorative Surfaces



EASILY ACCEPTS TOPCOAT



PREMIUM STAIN BLOCKER



MOISTURE PERMEABLE FINISH

NET CONTENTS: 5 Gallons

For Professional Use Only

*Disaster Restoration Products*