Piranha 2 is a heavy duty, fast acting paint remover for the **PRECAUTIONS** professional. Utilizing the power of methylene chloride, Piranha 2 will attack multiple layers of paint in a single BLINDNESS IF SWALLOWED. VAPORS ARE HARMFUL. SKIN application. Piranha 2 will remove most oil and latex paints. varnishes, shellacs, lacquers and enamels. Piranha 2 is nonflammable and will not raise the grain of wood or corrode metals. This product does not require anti-evaporation paper like many caustics or other weaker solvent formulas.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN Wear proper respiratory protection. Wear full body, protective CAÚSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN clothing for spray application. For indoor application, open CHILDREN, PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE, Wear a NIOSH approved respirator to control lead exposure. Carefully clean up constant supply of moving fresh air during use. Do not use in with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

other means to assure a constant supply of fresh moving air during use. Do not use Piranha 2 in poorly ventilated areas. Ideal working temperature is between 65°- 85°F. Avoid direct sunlight. Protect floor coverings and other areas not being stripped. Do not use on synthetic fabrics, plastic, linoleum, asphalt, foam products or rubber tile.

APPLICATION TOOLS

Apply Piranha 2 with brush or airless spray equipment.

Brush: Synthetic, nylon or polyester bristle Spray: .017 to .021 tips

PRODUCT APPLICATION

Stir well before using. Open pail carefully to avoid splashing. For best results, test a small area to determine the appropriate thickness, and duration of time required to most effectively remove the lead-based paint. Brush on a thick layer in one direction for best results. Brushing back and forth opens up the anti-evaporation barrier, which forms on the initial pass.

Allow Piranha 2 to work 5-15 minutes before performing a test scrape to determine how much paint has been lifted. Once Piranha 2 finishes removing the paint from the surface, scrape it away with putty knife, cloth or steel wool. Clean substrate with a mild detergent solution to remove any residues. Collect waste in a metal container and dispose of all waste in accordance with existing regulations. Piranha 2 does not require a neutralizer.

COVERAGE

Smooth Surfaces: 100 ft²/gal. Porous Surfaces: 50-100 ft²/gal

CLEANUP

Clean tools with a mild detergent solution to remove any residues. Dispose of all waste according to all existing local. state and federal regulations.

PRECAUTIONS: POISON. MAY BE FATAL OR CAUSE AND EYE IRRITANT, CONTAINS METHYLENE CHLORIDE, 2-BUTOXYETHANOL, METHANOL, TOLUENE, CANNOT BE MADE NONPOISONOUS. USE ONLY WITH ADEQUATE VENTILATION (MOVING FRESH AIR). Methylene chloride has been shown to cause cancer in laboratory animals. Risk to your health depends on level and duration of exposure. Spray application will increase concentration of methylene chloride vapors. Avoid breathing vapors and spray mists. all windows and doors or use other means to assure a basement or other unventilated areas. If eves water or nose becomes irritated, ventilation is inadequate. Avoid contact with skin or eyes. Exposure to open flame or hot surfaces For indoor application, open all windows and doors or use may produce toxic gases. Open container carefully and close after each use. Store locked up. Store Piranha 2 in original, labeled container only. Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Do not use on plastics. After unusually long exposure to the atmosphere, the material may dry out and become combustible. Dispose of contents/container in accordance with local/regional/ national/international regulations.

> NOTICE: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EYE: Immediately flush eyes with clean water for at least 15 minutes. If irritation persists, call a physician immediately.

SKIN: In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

INGESTION: If ingested, DO NOT induce vomiting; call a physician immediately. Poisonous if swallowed. Can affect the optic nerve resulting in blindness. Can cause mental sluggishness, nausea and vomiting leading to severe illness, possibly death.

INHALATION: Remove victim to fresh air. Give oxygen if there is difficulty breathing. Seek medical advice immediately. Refer to the Safety Data Sheet (SDS) available from your distributor or at www.fiberlock.com for further safety and handling instructions.



Professional Products **Professional Results**



HEAVY DUTY PAINT STRIPPER

Fast Acting Solvent Based Paint Remover

- Attacks up to 30 layers of paint
- Does not raise the grain of wood

MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. SKIN AND EYE IRRITANT. SEE SAFETY PRECAUTIONS ON SIDE PANEL.

For Professional Use Only NET CONTENTS: 5 Gallons

Paint Removal Products

DANGER! POISON! MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. SKIN AND EYE IRRITANT. USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS. **KEEP OUT OF REACH OF CHILDREN.**

Do not take internally. Close container after each use. Store between 40°F (4.5°C) and 90°F (32°C)

Do not use in areas where vapors can accumulate including basements, bathrooms and other confined spaces. DO NOT USE THIS PRODUCT IN POORLY VENTILIATED AREAS!

Do not use Piranha 2 until you have read and fully understand the SDS.

24 hour Emergency "CHEM-TEL" - 800.255.3924

FIBERLOCK PIRANHA 2 5720 DANGER | DANGER





H300 - Fatal if swallowed

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H351 - Suspected of causing cancer.

H371 - May cause damage to organs

Obtain special instructions before use.; Do not breathe dust/fume/gas/ mist/vapours/spray.; Do not eat, drink or smoke when using this product.; Use personal protective equipment as required.; Wear protective gloves/ protective clothing/eye protection/face protection.; See SDS for full list of

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.; IF exposed or concerned: Get medical advice/attention.; IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.: Specific treatment (see advice on this label).; Specific measures (see advice on this label).; Rinse mouth.: See SDS for full list of P phrases

Canadian Contact Info: 4050-B Sladeview Crescent Suite 200 Mississauga, ON L5L 5Y5 Canada

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

H300 - Mortel en cas d'ingestion.

H312 - Nocif par contact cutané.

H315 - Provoque une irritation cutanée.

H319 - Provoque une sévère irritation des yeux.

H351 - Susceptible de provoquer le cancer

H371 - Risque présumé d'effets graves pour les organes

Se procurer les instructions avant utilisation.|Ne pas respirer les poussières/ fumées/gaz/brouillards/vapeurs/aérosols. Ne pas manger, boire ou fumer en manipulant ce produit. Utiliser l'équipement de protection individuel requis.|Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage. Voir SDS pour la liste complète

EN CAS D'INGESTION: appeler immédiatement un CENTRE ANTIPOISON ou un médecin. IEN CAS d'exposition prouvée ou suspectée: Consulter un médecin. IEN CAS d'exposition ou de malaise: appeler un CENTRE ANTIPOISON ou un médecin Traitement spécifique (voir les conseils sur cette étiquette) Mesures spécifiques (voir les sur cette étiquette). Rincer la bouche. Voir SDS pour la liste complète des phrases P

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

Piranha, the Piranha Logo and other marks on this label are trademarks of ICP Construction, Inc.

5720-5



150 Dascomb Rd. Andover, MA 01810 (800) 342-3755 www.fiberlock.com

Rev. 10.17.18