



Professional Products  
Professional Results



# POST-REMOVAL SURFACE SEALANT


## Lock Down Residual Asbestos Fibers after Removal of ACM

- UL classified
- Class A fire rated
- Ideal for use as a pulldown
- Compatible with many floor adhesives

NET CONTENTS: 5 Gallons

For Professional Use Only

*Asbestos Abatement Products*



ENCAPSULANT MATERIALS  
AS TO FIRE RESISTANCE  
FOR USE WITH CLASSIFIED FIRE RESISTANCE  
TYPES RG, AND 106 CEMENTITIOUS MIXTURES CLASSIFIED FOR  
W. R. GRACE & CO.— CONSTRUCTION PRODUCTS DIVISION AND AT  
AN APPLICATION RATE OF 500 SQ. FT./GAL. ABILITY OF THIS MATERIAL TO ACT AS A SEALANT HAS NOT  
BEEN INVESTIGATED. SEE UL FIRE RESISTANCE DIRECTORY 95S1  
Fiberset PM Clear 7475 or Fiberset PM White 7470 are post removal encapsulant materials for use with  
Classified Types RG, and 106 cementitious mixtures manufactured by W. R. Grace & Co.— Construction  
Products Division, applied at an application rate of not less than 500 sq ft/gal to beams, columns, joists,  
roof-ceiling assemblies consisting of all fluted galvanized steel roof deck and floor-ceiling assemblies  
consisting of all fluted or cellular steel floor and form units or cellular/fluted blends provided that the  
underside of the units receives a coat of Type SK-3 prior to the application of the cementitious mixture.  
The ability of these materials to act as a sealant has not been investigated.

**CAUTION!**  
**KEEP OUT OF REACH OF CHILDREN.**  
Do not take internally.  
Close container after each use.  
Keep from freezing  
Store between 40°F (4.5°C) and 90°F (32°C)  
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

**FIBERLOCK FIBERSET PM WHITE 7470  
WARNING | ATTENTION**



H351 - Suspected of causing cancer.  
H351 - Susceptible de provoquer le cancer.  
H412 - Harmful to aquatic life with long lasting effects.  
H412 - Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Obtain special instructions before use.; Use personal protective equipment as required.; Avoid release to the environment.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation. Utiliser l'équipement de protection individuel requis. Éviter le rejet dans l'environnement. Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin. Voir SDS pour la liste complète des phrases P

**Canadian Contact Info:**  
**4050-B Sladeview Crescent Suite 200**  
**Mississauga, ON L5L 5Y5 Canada**

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

Fiberset PM, the Fiberset PM Logo and other marks on this label are trademarks of ICP Construction, Inc.

# 7470-5 White



150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)  
Rev. 10.16.18

Fiberset PM is a pre-mixed "lockdown" sealing treatment for microscopic residual fibers present after the removal of Asbestos Containing Material (ACM). Available in white, blue or clear, Fiberset PM is a ready-to-use, Class A fire rated coating that provides a flexible barrier over residual fibers to ensure final air clearance. Fiberset PM is UL® classified for use as a primer for fireproofing replacement materials under the "Encapsulant Materials" section of the UL directory, and is compatible with leading brands of flooring adhesives. Fiberset PM is a water based coating that employs advanced 100% acrylic resin technology to extend the life expectancy of airless spray equipment.

### SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION TOOLS

Apply Fiberset PM with airless spray equipment. Use the settings below when applying Fiberset PM:

Spray: .015-.021 tip @ 1700-3000 P.S.I

### PRODUCT APPLICATION

Stir Fiberset PM thoroughly to achieve a uniform consistency. Fiberset PM is pre-mixed; water-addition is not necessary. Minimum application temperature: 45°F.

LOCKDOWN - Sealing microscopic residual fibers after asbestos removal is mandatory on every project. Prior to post-removal air monitoring, apply one coat to all exposed surfaces. Fiberset PM has been accepted as part of a UL Classified Fireproofing System for use with Retro-Guard® manufactured by W.R. Grace. Coverage should not be less than 500 sq. ft. per gallon on smooth surfaces.

PULL DOWN BY MISTING - Misting the contaminated air is an effective technique prior to post-removal air monitoring. To pull down free-floating asbestos fibers effectively, stand in the center of the room and hold the spray gun as close to the ceiling as possible. A mist should be sprayed parallel to the ceiling in every direction or in a circle. Apply one coat to the polyethylene sheeting on the walls and floor prior to dismantling containment.

### COVERAGE

Lockdown: Not less than 500 sq. ft. per gallon.

### DRYING TIME @ 70°F 50% R.H

To Touch: 1-2 hours  
To Recoat: 1-2 hours

### CLEANUP

Tools and drippings should be cleaned with warm soapy water before coating dries. Follow equipment manufacturer's directions to clean spray equipment. The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

### PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Keep closures tight and containers upright to prevent leakage. Product is non-combustible. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.