



Professional Products
Professional Results



POST-REMOVAL SURFACE SEALANT


Lock Down Residual Asbestos Fibers after Removal of ACM

- UL classified
- Class A fire rated
- Ideal for use as a pulldown
- Compatible with many floor adhesives

NET CONTENTS: 5 Gallons

For Professional Use Only

Asbestos Abatement Products



ENCAPSULANT MATERIALS
AS TO FIRE RESISTANCE
FOR USE WITH CLASSIFIED FIRE RESISTANCE
TYPES RG, AND 106 CEMENTITIOUS MIXTURES CLASSIFIED FOR
W. R. GRACE & CO.— CONSTRUCTION PRODUCTS DIVISION AND AT
AN APPLICATION RATE OF 500 SQ. FT./GAL. ABILITY OF THIS MATERIAL TO ACT AS A SEALANT HAS NOT
BEEN INVESTIGATED. SEE UL FIRE RESISTANCE DIRECTORY 95S1
Fiberset PM Clear 7475 or Fiberset PM White 7470 are post removal encapsulant materials for use with
Classified Types RG, and 106 cementitious mixtures manufactured by W. R. Grace & Co.— Construction
Products Division, applied at an application rate of not less than 500 sq ft/gal to beams, columns, joists,
roof-ceiling assemblies consisting of all fluted galvanized steel roof deck and floor-ceiling assemblies
consisting of all fluted or cellular steel floor and form units or cellular/fluted blends provided that the
underside of the units receives a coat of Type SK-3 prior to the application of the cementitious mixture.
The ability of these materials to act as a sealant has not been investigated.

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally.
Close container after each use.
Keep from freezing
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

**FIBERLOCK FIBERSET PM CLEAR 7475
WARNING | ATTENTION**



H351 - Suspected of causing cancer.
H351 - Susceptible de provoquer le cancer.
H412 - Harmful to aquatic life with long lasting effects.
H412 - Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Obtain special instructions before use; Use personal protective equipment as required; Avoid release to the environment; See SDS for full list of P phrases

Se procurer les instructions avant utilisation; Utiliser l'équipement de protection individuel requis; Éviter le rejet dans l'environnement; Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin; Voir SDS pour la liste complète des phrases P

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

Fiberset PM, the Fiberset PM Logo and other marks on this label are trademarks of ICP Construction, Inc.

7475-5 Clear



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.16.18