



Professional Products
Professional Results



6000HD

Heavy Duty Mold Resistant Coating* WHITE (Tintable)

- Ideal for porous material
- High build formula for one coat coverage
- Class A fire rated

*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

8362-5 White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.16.18

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally.
Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

Calculated VOC: 91 g/l
FIBERLOCK IAQ 6000HD 8362
DANGER | DANGER



H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H317 - May cause an allergic skin reaction.
H351 - Suspected of causing cancer.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

H315 - Provoque une irritation cutanée.
H319 - Provoque une sévère irritation des yeux.
H317 - Peut provoquer une allergie cutanée.
H351 - Susceptible de provoquer le cancer .
H372 - Risque avéré d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
H411 - Toxique pour les

Obtain special instructions before use.; Do not breathe dust/fume/gas/mist/vapours/spray.; Wear protective gloves/protective clothing/eye protection/face protection.; Use personal protective equipment as required.; Do not eat, drink or smoke when using this product.; Avoid release to the environment.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation.|Ne pas respirer les poussières/fumées/gaz/ brouillards/vapeurs/aérosols.|Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage.|Utiliser l'équipement de protection individuel requis.|Ne pas manger, boire ou fumer en manipulant ce produit.|Éviter le rejet dans l'environnement.|Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label).; Take off contaminated clothing and wash before reuse.; IF ON SKIN: Wash with plenty of soap and water.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; Get medical advice/attention if you feel unwell.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin.|Traitement spécifique (voir les conseils sur cette étiquette).|Enlever les vêtements contaminés et les laver avant réutilisation|EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon.|EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.|Consulter un médecin en cas de malaise.|Voir SDS pour la liste complète des phrases P

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

IAQ 6000HD is a white, tintable, high-build coating for use during new building construction. IAQ 6000HD contains a fungistatic agent to resist mold growth on the dry coating surface. IAQ 6000HD is a durable and flexible 100% acrylic water based flat coating. IAQ 6000HD is designed for use on non-porous and semiporous building materials including gypsum wallboard, orientedstrand board (OSB), wood framing timbers, plywood, masonry block, and many other structural surfaces where a flexible, high-build mold resistant coating is necessary.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWaveRTU.

Patch irregularities with vinyl patching paste or an appropriate patching compound. IAQ 6000HD is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

WALLBOARD, SHEETROCK, GYPSUM BOARD – Joint cement should be sanded smooth, but avoid abrading the paper.

FERROUS METAL – Clean, then prime with IAQ 4000 rust inhibiting direct-to-metal primer.

WOOD – Seal knots and stains with IAQ 5000 stain-blocking primer.

MASONRY BLOCK – Apply one coat of IAQ 3000 block filler if a denser surface is desired.

APPLICATION TOOLS

Apply IAQ 6000HD with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer
- Spray: .021 to .025 tip @ 2000-2800 P.S.I.

TINTING

IAQ 6000HD may be tinted to any off-white or pastel based color. Add up to 2 oz. of universal colorant per gallon. Start with 50% of the tinting formula and adjust as necessary.

PRODUCT APPLICATION

IAQ 6000HD is supplied ready to use, but can be thinned sparingly with water (up to ½ pint water per gallon) for proper application consistency if necessary. Apply IAQ 6000HD generously and uniformly by brush or airless spray. Ensure that the finished surface is properly sealed. To ensure that the finished surface is properly sealed, two-coats may be required on some highly porous surfaces.

COVERAGE

- Smooth Surfaces: 250-400 ft²/gal.
- Porous Surfaces: 100-300 ft²/gal.

DRYING TIME @ 70°F 50% R.H

- To Touch: 1-2 hours
- Recoat: 8-16 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 6000HD dries. The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Keep closures tight and containers upright to prevent leakage. Product is non-combustible. Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. IAQ 6000HD is resistant to the deteriorating action of mold and mildew. No claim is made for the preservative action other than to the coating film. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F, when drying conditions are poor or when surfaces are above a 11% moisture level content. Use adequate ventilation during application. For interior use only.