



2432-U	4"x9' (60 Rolls)
2433-U	6"x9' (40 Rolls)
2434-U	8"x9' (30 Rolls)

Wet-Wrap 'N' Seal

Benefits

- *Applies quickly and easily*
- *Free of fumes and odors*
- *Permanently shaped*
- *High strength*
- *Pre-cut to 9 ft (2.7 m) lengths*
- *One-step installation*
- *Saves time and labor*
- *No maintenance*
- *No waste*
- *No special skills or tools required*

Product Description

Wet-Wrap 'N' Seal is a permanent, water activated insulation encasement and repair system.

It applies quickly and easily to pipes, breeching, valves, duct work and other fittings. Once dry, it permanently retains its strength, shape and form. Wet Wrap 'N' Seal is the lowest cost encasement material available and is free of any fumes or strong odors.

Wet-Wrap 'N' Seal is available in 9 ft rolls with 4 in., 6 in., or 8 in. widths.

Surface Preparation

Prior to application it is important to determine if the existing asbestos matrix is well adhered to the substrate. Correct any surface defects and clean all surfaces thoroughly. Be careful not to agitate asbestos fibers during preparation; this could increase asbestos exposure.

If damaged, first apply a light collating of SerpiFlex followed by a second application. The second application should saturate the damaged area.

Apply additional fiberglass, mineral wool or insulation cement to treated area if needed.

Application

Water in pail must be clean at all times. This product is a plaster of paris and synthetic resin combination. Use of skin protection or gloves is recommended.

1. Hold loosely and submerge one Wet-Wrap 'N' Seal roll at a time in clean, tepid water (68°F/20°C) for 5 seconds. Keep thumb under edge of Wet-Wrap 'N' Seal to avoid difficulty in finding starting end after squeezing.

2. Remove and squeeze with twisting motion to wring out excess water, keeping thumbs under starting end.
3. When applying overlap each layer by 50%. Smooth each overlap turn of Wet-Wrap 'N' Seal into the layers below, molding carefully to the contour, forming a solid, well-fused covering.

Note: For leather-tough protection and added strength, you can apply SerpiMastic over the Wet-Wrap 'N' Seal after it is dry.

Setting Time

Wet-Wrap 'N' Seal will set in 2-4 minutes. Setting time is measured from the point when the product is immersed to the point when it can no longer be molded. Increasing or decreasing the temperature of the immersion water by 9°F (5°C) will reduce or extend the setting time by approximately 15 seconds.

Cleanup

Tools and drippings should be cleaned with warm soapy water before adhesive dries. Dispose of waste according to all existing local, state and federal regulations.

Precautions

Store in a dry place. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.

Availability

Wet-Wrap 'N' Seal is available through authorized Serpi Systems distributors.

Product Availability
Wet-Wrap 'N' Seal is available through authorized Serpi Systems distributors in the following quantities:

Description	Part No.	Std. Pack
4" x 9'	2432-U	60 Rolls
6" x 9'	2433-U	40 Rolls
8" x 9'	2434-U	30 Rolls

For Technical Assistance call toll free at 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of this product for each specific project and for the health and safety of personnel working in the area.

The Serpi Systems Logo, SerpiFlex, SerpiMastic, SerpiFactant, Wet-Wrap 'N' Seal, the slogans, product labeling and other marks in this brochure are the trademarks of Fiberlock Technologies, Inc. ©2012 Fiberlock Technologies. All rights reserved.